

Matte Finish Protective Wax

FILAMATT



TERRACOTTA, QUARRY TILE, UNPOLISHED NATURAL STONE



GIVES THE SURFACE A NATURAL FINISH.

PROTECTS PLASTERED AND ENGINEERED STONE WALLS.



Coverage:

1 Liter (1.06 QT)

Terracotta ▶ 323 sq.ft. (30 m²)

Stone ▶ 323-430 sq.ft. (30-40 m²)

Coverage rates are indicative and per coat.



Packaging:

1 Liter (1.06 QT) 6 plastic bottles per box

WHAT IT'S FOR

- Maintains terracotta, quarry tile, tumbled marble and natural stone.
- Provides the surface with a durable, low sheen, natural finish.
- Ideal finishing coat over a water-based or solvent sealer.
- Prevents dust from settling and staining terracotta and natural stone.
- When FILAMATT is polished, it gives the surface a satin finish.

ADVANTAGES

- Easily removed.
- Highly concentrated – can be diluted according to use.
- Essentially self-leveling due to its consistency.

HOW TO USE IT

Instructions:

Surface treatment: Dilute FILAMATT by 1:30 adding 10 oz. of water to a gallon of wax. Apply the diluted product with a clean cloth or lambswool applicator and let dry for about an hour. Apply a second coat perpendicular to the first. Do not walk on the floor for an hour after the second application. The product can be used undiluted to tone down the gloss of a previous surface treatment.

Routine maintenance: Dilute by adding 10-15 oz of FILAMATT to a gallon of water. FILAMATT can be used to routinely wash and wax surfaces.

Caution: Wax application is not recommended on exterior surfaces, in wet environments and any place with standing water. FILAMATT can be removed with FILAPS87.

Fila Chemicals USA, Corp.
Miami, FL 33172
tel +1-305-513-0708
filausa@filasolutions.com

TOLL FREE 1-844-FILA123



Recommended by over
200 INTERNATIONAL TOP BRANDS
manufacturers of materials for floors and wall coverings
usa.filasolutions.com