



- TERRACOTTA
- QUARRY TILES
- UNPOLISHED STONE AND AGGLOMERATES



WHAT IT'S FOR

- Protects unpolished natural stone (limestone, sandstone, slate, etc.) vitrified quarry tiles and various types of terracotta.
- Ideal both for treatment and maintenance.

ADVANTAGES

- The product is self-polishing, but can also be polished to restore or increase shine.
- A 3-in-one solution: protects, maintains and gives floors an excellent finish.
- Original new satin look.
- Ideal to create prestigious floors: enhances the beauty of the surface.
- Easy to apply and maximum coverage.
- Does not degenerate with maintenance.

HOW TO USE IT

Dilution: either undiluted or diluted according to requirements.

Using a cloth or other applicator, apply an even layer of the product onto a clean dry floor surface. After one hour, apply a second coat at right-angles to the first. The floor is ready to walk on after about half-an-hour. For better sheen, buff with a floor polisher or a lint free cloth.

An initial protection coat of FILAFOB water-repellent protector is recommended on highly absorbent terracotta and stone (such as limestone, sandstone and travertine) or FILAW68.

For maintenance:
Restoring sheen (every 2-3 months): after cleaning the surface with a diluted solution of FILACLEANER (1:200), apply FILASATIN diluting 500 ml of product in 5 litres of water: For greater shine, wait till floor is dry (after about 1 hour) and buff with a wool cloth or floor polisher.

Renewing protection (once a year): apply undiluted wax with a cloth, fleece pad or other applicator. Buff the surface when it is dry (after about 1 hour).

COVERAGE

With one litre:

Terracotta	30 m ²
Stone	30/40 m ²

"Coverage shown is for guidance purposes only and refers to single coats"

Packaging

- 1 litre cans in boxes of 12.
- 5-litre cans in boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Protect can from frost. Store at room temperature.

TEMPERATURES

Storage temperature: from 5° to 30° C
 The product must be applied to material with a temperature of between 10° and 30°C.

COMPOSITION

Emulsion of synthetic wax, polymer suspensions, fragrance and appropriate additives.

LABELLING

No safety and risk labelling or instructions are required, as the product is not classified as hazardous under current regulations.

Safety data sheet available on request.

Contains: reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

TECHNICAL FEATURES

Appearance: liquid
Colore: milky white
Odour: floral bouquet
Density: 1.010 kg/l
pH: 8.1

This information is the result of our most up-to-date technical know-how and is based on ongoing laboratory research and testing. Nevertheless, for reasons beyond our control, any suggestions always require appropriate analysis, testing and monitoring. Fila shall not accept any responsibility for improper use of its products.